

1. Product Profile

StenBacker is a closed cell polyethylene (PE) rod.

2. Uses

StenBacker is used for adjusting joint depths and to constitute barriers against flow in sloped joints.

3. Types

It is available in diameters of 6mm, 8mm, 10mm, 12mm, 15mm, 20mm, 25 mm, 30mm, 35mm, 40mm, 50mm, 60 mm and 70 mm.

4. Application

Diameter of the **StenBacker** joint backer rods must be 10 – 25% larger than the joint width; and the rod must be fitting tightly in the joint.

5. Safety

Required safety measures must be observed during the application of the material and the applicators must use protective clothing, gloves and goggles. Applicators and supervisors must read Material Safety Data Sheet (MSDS) of the material.

6. Storage

It must be stored in confined storages and kept away from sunlight. It must not be allowed to get wet or moist. Stored properly, the shelf life of **StenBacker** is 36 months.

Closed Cell Polyethylene Rod

Highlights

- Prevents sealants to adhere to the bottom of the joint and ensures better compensation for floor movements
- Adjusts joint depth and supports proper operation of the joints
- Lowers the costs by preventing unnecessary sealant use.

7. Company Liability

The information contained in this document is based on site experience of and laboratory tests done by **Stenkim**® and meant to give general information. It is the purchaser's responsibility to ensure applicability of products to their use. All **Stenkim**® products are available in specified quality and conditions. The company accepts no liability whatsoever unless the transportation, storage, application conditions and customer use are overseen by **Stenkim**®. **Stenkim**® reserves the right to update all information contained in this document without notice.